



**PRODUCT CATALOG**

- New Products NEW
- **Sound Level Meter**
- Vibration Meter
- Light Meter
- Humidity Temperature Meter
- Particle Counter
- CO/ CO<sub>2</sub> Tester
- Infrared Thermometer
- Thermometer
- EMF Tester
- PH Meter
- Power Clamp Meter
- Harmonic Clamp Meter
- Battery Impedance Tester
- Solar Power Meter
- Flexible Clamp Meter
- Anemometer/ Tachometer
- Multimeter
- Milli / Micro Ohm Meter
- Earth/ Ground Tester
- Insulation tester
- Clamp Meter
- Calibrator
- Lan Cable Tester
- Power Supply
- Accessories

☑ **Sound Level Meter**

Home > Products > DC/AC Sound Level Meter > Programmable Sound Level Meter



**TES-1352S**  
**Programmable Sound Level Meter**

**Product Features**

- Compliant with IEC 61672-1 class2 standard.
- Easy to use for Maximum level and
- Peak level can be measured simultaneously.
- Dynamic range of 60dB
- Five range from 30 to 130dB
- A&C Frequency Weighting
- Fast/Slow dynamic characteristic
- 200M Records Data logging function (micro SD CARD 4GB)
- USB interface
- Sound Level Alarm Output
- Real time clock with calendar

Applicable standards	IEC61672-1: 2013 Class 2, ANSI S1.4: 1983 Type 2
Measurement item	SPL, MaxL
Measurement level	30dB to 130dB
Linearity range	60dB
Measurement frequency range	31.5 Hz to 8KHz
Frequency weight	A and C
Time weight	Fast, Slow
Accuracy	±1.0dB (ref 94dB @1KHz)
Microphone	1/2 inch Electret condenser microphone
Measurement level range	5 ranges in 10-dB step :30 ~ 90dB , 40 ~ 100dB , 50 ~ 110dB , 60 ~ 120dB , 70 ~ 130dB
Digital display	4 digit LCD , 0.1dB resolution, updated every 1s
Quasi-analog bar indicator	1-dB steps, 60dB display range , updated every 0.125s
Display Warning function Overrange indicator Underrange indicator	Displayed at the upper limit Displayed at the lower limit
Analog AC / DC output	2Vrms ( at full scale ) , 10mVDC / dB
Power supply	Four 1.5V LR-6/AA size cell, AC adaptor
Battery Life	about 24 hours
Operating temperature , humidity	-10°C to 50°C (14°F to 122°F) R.H. < 90% non-condensing
Dimensions	265 (L) × 72(W) × 21(H)mm, ( 10.4" L × 2.8" W × 0.8" H )
Weight	Approx. 310g
Accessories	Instruction manual , Battery , Carrying case , Adjustment screwdriver shield, USB connecting cable, 3.5ϕ plug
Optional accessories	Microphone extension cable, AC Adaptor



• BACK •

• INQUIRY •



© 2014 by TES Electrical Electronic Corp. All rights reserved. Tel: 886-2-2799-3660 Fax: 886-2-2799-3669 Add: 7F, No. 31, Lane 513, Rui Guang  
[About Us](#) | [News](#) | [Products](#) | [Application](#) | [Online Inquiry](#) | [Product Registration](#) | [Software](#) | [Contact Us](#) | [Jobs](#)