

SHANGHAI  
YIHUA **V&A**  
INSTRUMENT CO., LTD.



Digital multimeter

**Products**
[Infrared thermometer](#)
[Digital multimeter](#)
[Clamp meter](#)
[Cable tester / Line tracker](#)
[Professional test instrument](#)
[Analogue multimeter](#)
[DC Power supply](#)
[Accessory](#)
**Digital multimeter**

- VA16
- VA19
- VA17 / VA15 Series
- MS8221 Series
- MY60 Series
- M3900
- M300 / M320
- **MAS830 Series >**
- M830 Series



CATALOGUE REQUEST

**MAS830 SERIES DIGITAL MULTIMETER**

MAS830 / MAS830B / MAS838 / MAS830L


**MAS830**

- Display: 1999, Digital is 15mm high
- DC Voltage: 200m / 2V / 20v / 200v  $\pm 0.5\%$ , 600V  $\pm 0.8\%$
- AC Voltage: 200 / 600V  $\pm 1.2\%$
- DC Current: 200 $\mu$  / 2m / 20mA  $\pm 1.0\%$ , 200mA  $\pm 1.5\%$ , 10A  $\pm 3.0\%$
- Resistance: 200 / 2K / 20K / 200K  $\pm 0.8\%$ , 2M $\Omega$   $\pm 1.0\%$
- hFE: 1- 1000
- Diode Test
- Data Hold
- Continuity Test
- Power: 6F22(9V) x1
- Size: 138 x 69 x 31mm
- Weight: Approx.170g(including battery)


**MAS830B**

- Display: 1999, Digital is 15mm high
- DC Voltage: 200m / 2V / 20 / 200v  $\pm 0.5\%$ , 600V  $\pm 0.8\%$
- AC Voltage: 200 / 600V  $\pm 1.2\%$
- DC Current: 200 $\mu$  / 2m / 20mA  $\pm 1.0\%$ , 200mA  $\pm 1.5\%$ , 10A  $\pm 3.0\%$
- Resistance: 200/2K/20K/200K $\pm 0.8\%$  2M $\Omega$  $\pm 1\%$
- hFE: 1 ~ 1000
- Diode Test
- Data Hold
- Power: 6F22(9V) x1
- Size: 138 x 69 x 31mm
- Weight: Approx.170g (including battery)


**MAS838**

- Display: 1999, Digital is 15mm high
- DC Voltage: 200m / 2V / 20 / 200V $\pm 0.5\%$ , 600V  $\pm 0.8\%$
- AC Voltage: 200 / 600V  $\pm 1.2\%$
- DC Current: 200 $\mu$  / 2m / 20mA  $\pm 1.0\%$ , 200mA  $\pm 1.5\%$ , 10A  $\pm 3.0\%$
- Resistance: 200 / 2K / 20K / 200K / 2M $\Omega$  $\pm 1.0\%$
- Temperature: -20 ~ 0C10%, 0 ~ 400C $\pm 1.0\%$ , 400 ~ 1000C  $\pm 2.0\%$
- hFE: 1 ~ 1000
- Diode Test
- Data Hold
- Continuity Test
- Power: 6F22(9V) x 1
- Size: 138 x 69 x 31mm
- Weight: Approx.170g (including battery)

**MAS830L**

- Display: 1999, Digital is 15mm high
- DC Voltage: 200m / 2V / 20 / 200V  $\pm 0.5\%$ , 600V  $\pm 0.8\%$
- AC Voltage: 200/600V  $\pm 1.2\%$
- DC Current: 200 $\mu$  / 2m / 20mA  $\pm 1.0\%$ , 200mA  $\pm 1.5\%$ , 10A  $\pm 3.0\%$
- Resistance: 200 / 2K / 20K / 200K  $\pm 0.8\%$ , 2M $\Omega$   $\pm 1.0\%$
- hFE: 1 ~ 1000



- Diode Test
- Data Hold
- Back Light
- Continuity Test
- Power: 6F22 (9V) x1
- Size: 138 x 69 x 31mm
- Weight: Approx.170g (including battery)

| [HOME](#) | [ABOUT V&A](#) | [PRODUCTS](#) | [NEW PRODUCTS](#) | [SERVICE](#) | [TRADE SHOW](#) | [CONTACT US](#) | [SITE MAP](#) |

Copyright 2005 SHANGHAI YIHUA V&A INSTRUMENT CO.,LTD. All Rights Reserved