

1318 Platinum RTD Thermometer

FEATURES:

- Pt 3916/3926/385 RTD standard.
- 7500 DataLogging capacity. (1317)
- Warning beeper with HI/LO setting.
- Time setting.
- MAX / MIN with TIME, MAX-MIN AVG Hold function.
- °C / °F / K User-Selective.
- Back - Light LCD display.
- Dual input function T1/T2 temperature display. (1318)



SPECIFICATIONS:

Measuring Range	-200 to +800 (-328 to +1472)
Resolution	0.1 / 0.1 / 0.1K
Accuracy	±(0.05%rdg+0.2) ±(0.05%rdg+0.4)
Datalogger (1317)	7500 reading
Temperature Coefficient	Less than 0.1 times the applicable accuracy specification per ()
Sampling Rate	1 time/sec
Operating/ Storage Conditions	0 ~ 40 < 80% RH , -10 ~ 60 < 70%RH
Power Source	6 pcs size AAA Battery
Battery Life	Approx. 300hours. (not including backlight and beeper)
Size	152(L)×72(W)×37(H)mm
Weight	Approx. 300g
Accessories	1. Instruction manual, Battery, RTD plug. 2. Software for WINDOWS™, RS-232 Cable, 9 pin to 25 pin Gender changer. (1317)