

TES-1340 Hot-Wire Anemometer



FEATURES

Fast Response Probe.

Air Flow Volume

Instant / Avg / 2/3 Vmax Flow Measurement.

Velocity m/s, ft/min, knots, km/hr, mph.

Data hold & Maximum / Minimum function.

Manual data memory and read function (10 x 99 sets).

LCD triple display.

Auto power off function ON / OFF Time setting.

Backlight function ON / OFF Time setting.

Snake telescoping probe.



SPECIFICATION

	Measuring Range	Resolution	Accuracy
Air Flow	0.1 to 30.0 m/s	0.01 m/s	±3% of reading ± 1%FS
	0.2 to 110 km/hr	0.1 km/hr	
	10 to 6000 ft/min	1 ft/min	
	0.1 to 59 knots	0.01 knots	
	0.12 to 68 MPH	0.01 MPH	
Air Flow Volume	0 to 999900 CFM	0.001 CFM	
	0 to 999900 CMM	0.001 CMM	

Response time

1 second

Manual Memory Capacity

10 x 99 sets. (Direct reading from LCD display)

Operating Conditions	0°C ~ 50°C (32°F ~ 122°F), ≤80% R.H.
Power Source	6 pcs size AAA Battery
Battery Life	Approx. 10 hours
Size	135(L) x 72(W) x 31(H)mm
Weight	Approx. 400g (including Probe)
Accessories	Instruction manual, Battery, Carrying case



TES Electrical Electronic Corp.

Office: 7F, No. 31, Lane 513, Rui Guang Road, Neihu Dist.,
 Taipei, Taiwan, R.O.C
 TEL:886-2-2799-3660 FAX:886-2-2799-5099
 E-Mail: tes@ms9.hinet.net